

AQUASHIELD Filler

FLEXIBLE WATER BASED WALL FILLER

Product Description:

A ready mixed Flexible filler with easy sanding properties for the filling of cracks, holes and the smoothing of uneven surfaces.

Recommended Uses:

Suitable for interior and exterior use only as a thin coat putty for the finishing of rough surfaces and as filler for small cracks, holes and surface imperfections. Also suitable for repair work of interior plaster, fair – faced and lightweight concrete.

Technical Properties:

Appearance	: flat.
Volume Solids	: 73% ± 2%.
Colour	: white & limited shades on request.
Pack Size	: 1- and 4-gallon plastic pail.
Spreading Rate	: 3.2 m ² / kg / at 100µ dft. Depending on end use application method and thickness applied.
Drying Time	: Surface dry in 1 hour. Re-coat able with itself after 2 hours and paintable after 10 hours. (in normal drying conditions).
Shelf Life	: 12 Months when stored in dry and cool conditions.

Application Data:

Mix well before use. Apply by trowel, filling knife or

spray. Apply sufficient AQUASHIELD Flex to fill or smooth surface.

Thinning	: Do not thin, supplied ready for use.
Cleaning	: Clean all tools and equipment immediately after use with clean water.

Specification:

Surface Preparation:

All surfaces should be sound, clean, dry and free from loose and flaking material, dirt, efflorescence, oil, and curing compounds, from release agents, laitance and organic growth.

Unstable surfaces (powdery or chalky) should receive a coat of AQUASHIELD X before filling.

Notes:

- Organic growth (moss, fungus, mildew) should be treated with a biocide in accordance with manufacturer's instructions.
- New cement, plaster and concrete must have had ample opportunity to dry before filling (minimum 15 days)
- On very dry absorbent surfaces wet the surface with sweet water prior to using the filler.

Safety Information:

Use only in well-ventilated areas. Do not breathe vapour/spray. In case of contact with eyes, rinse immediately with plenty of sweet water and seek medical advice.

