

## FIX-10-S

Plugging cement, fast-hardening cement



Material number	Contents	Unit of quantity	Packaging	Colour
201819001	6	KG	Bucket	Cement grey
201819002	12	KG	Bucket	Cement grey

### Product features

Very rapid setting (setting starts after water absorption)

### Advantages

- Chloride-free
- Immediate waterproofing

### Areas of application

- As immediate waterproofing against surface moisture penetrations, water ingress and seepage points
- For interior and exterior use

### Technical Data

#### Material properties

Product components	1 component system
Base material	Special cement
Consistency	Powder
Grain size max	< 0.5 mm
Start of solidification	Immediately after water absorption

#### Application

Substrate/application temperature	from 5 °C to 30 °C
Pot life	approx. 1 minutes
Consumption per litre - voids	approx. 2 kg/l

### Application technology

#### Aids/tools

- Protective gloves
- Trowel

## FIX-10-S

### Substrate preparation

Requirement for substrate

1. Firm
2. Load-bearing
3. Clean
4. Free of adhesion inhibiting substances

Preparing the details

For better anchoring of FIX 10-S, chisel out the leak position in a dovetail shape.

Preparing the surface

Remove loose pieces of plaster and masonry.

### Usage

Application

Press in FIX-10-S in dry form by hand. Repeat the procedure if the seal is not tight enough.

### Storage conditions

Storage

Cool, dry, protected from sunlight. Min. 12 months in the original container.

### Disposal

Product leftovers can be disposed of in accordance with disposal code AW 17 01 01.

### Notes

- Protect surfaces that are not to be treated from the effects of FIX-10-S!
- Appropriate preliminary tests must be carried out.
- FIX-10-S must not be mixed with plaster or brought into contact with plaster.

### Observe applicable safety data sheet!

GISCODE: ZP1

The rights of the buyer with regard to the quality of our materials are based on our terms and conditions of sale and delivery. Our technical advice team will be happy to advise you in the case of requirements that exceed the scope of the application described here. In order to be binding, a legally binding written confirmation is required. The product description does not release the user from a duty of care. Lay a test area in the event of uncertainty. This version becomes invalid in the event of a new version being issued.