

Stonecrete Sealer

FLOOR & WALL SEALER

Product Description:

This high-performance acrylic sealer is designed to protect and enhance concrete and stone surfaces. Its advanced formula penetrates deep for superior adhesion, offering long-lasting protection against weather, stains, and UV damage. Ideal for both interior and exterior use.

Areas of Application:

It can be applied on stone surfaces (natural and artificial), concrete, terrazzo tiles, and terracotta. It can be applied on both horizontal and vertical surfaces (floors & walls).

Features & Benefits:

- Enhances and protects the natural beauty of stone and concrete.
- Resistant to stains, water, and fading.
- Easy application with a roller, sprayer, or brush.

Technical Properties:

Basis	: Acrylic.
Colour	: Clear.
Consistency	: Liquid.
Density*	: 1.02
Weight solids	: 24%
Coverage (on a smooth surface)	: 8 – 12m ² /l per coat.
Dilution	: Not recommended.
*Drying time	: Touch dry 3-4 hours. Recoat 24 hours. Light traffic 24 hours. Normal traffic 72 hours.

Substrate:

All surfaces must be clean, dry and free of grease, oil and other contaminants. Can be applied on green concrete. Repair any cracks and then sand to a sound surface.

Directions for Use:

1. Surface Preparation: Ensure the surface is clean, dry, and free of dust, grease, and oils.
2. Application: Stir or shake well before use. Apply in thin, even coats using a roller, sprayer, or brush. Allow each coat to dry for 1–2 hours before applying the next.
3. Coverage: Approximately 80–120 sq. ft. per ltr / coat, depending on porosity.
4. Dry Time: Light foot traffic in 24 hours. Fully cures in 72 hours.

Cleaning:

All Tools should be cleaned with soapy water before the product dries out.

Packaging:

Available in 1ltr, 6 ltrs. and 25 ltrs. plastic pails.

Storage & Shelf Life:

Store in frost-free environment away from direct sunlight and maintain an ambient temperature of 25°C. Given these conditions, it will remain for 12 months in the original unopened packaging, use opened packaging promptly.

