

ASO[®] Unigrund-P

READY TO USE PRIMER AND SEALER

Product Description:

- Rapid drying.
- Universal application.
- Resistant to water and alkalis.
- Solvent free.

Areas of application:

ASO[®] Unigrund-P reduces the absorption of substrates, binds surface dust, consolidates, and prevents rapid water loss from levelling compounds. ASO[®] Unigrund-P is used for priming absorbent and lightly sanded substrates e.g., gypsum-based construction materials (plaster, interlocking gypsum slabs, boards, screeds), concrete, masonry work, marble, granite and similar substrates. Suitable as an adhesion promoter for surface-applied waterproof membranes (e.g., SANIFLEX, AQUAFIN[®]-2K/M), thin bed adhesives such as LIGHTFLEX, MONOFLEX-XL, SOLOFLEX, AK7P, UNIFIX as well as wall and floor levelling compounds such as SOLOCRET-15, SOLOPLAN[®] 30-PLUS and ASO[®] NM15. It is also suitable for exterior use.

Technical Data:

Basis	: acrylate dispersion.
Colour	: white.
Application/ Substrate temperature	: + 5° C to +30° C
Specific gravity	: 1.06
Cleaning	: whilst still fresh, with water.

Storage

: frost free, 15 months in the original unopened packaging. Use opened packaging promptly.

Substrate Preparation:

The substrate must be load-bearing, clean, dry, and free from materials, which will impede adhesion. Flow screeds must be abraded and vacuumed. Remove unstable or weakly bonded layers e.g., release agents, residues of old adhesive, levelling layers, surface finishes and paints, by mechanical scrubbing, planning, scabbling or shot blasting.

Product preparation:

ASO[®] Unigrund-P is ready to use. Application is with a paint brush, brush or a fine-pored sponge roller but it can also be sprayed with suitable equipment. Avoid applying too thickly or forming puddles. ASO[®] Unigrund-P must be fully dry before further work can be carried out on the primed surface.

Advice:

- The primer must be dry before applying the next coat.
- Protect areas not being treated with ASO[®] Unigrund-P.
- Do not apply wet in wet.
- Wash off splashes immediately.

